



FITTING INSTRUCTIONS FOR LP0056BK LICENCE PLATE HOLDER TRIUMPH STREET TRIPLE 675 2007- & STREET TRIPLE R 2008-



PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

YOU WILL NEED THE FOLLOWING TOOLS TO COMPLETE THIS JOB

Socket set to include 8mm, 10mm, 12mm and 13mm sockets and wrench.

Set of metric allen keys to include 3mm, 4mm and 5mm A/F sizes.

Phillips screwdriver.

12mm open-ended spanner.

Electrical stripping and crimping pliers.

Heat gun (or hair dryer).

Small amount of Super-Glue.

PLEASE READ ALL INSTRUCTIONS BEFORE COMMENCING


FITTING INSTRUCTIONS

- Remove seat (using key lock).
- Remove rear seat panels left and right side.
- Undo and remove the four nuts and bolts as arrowed in picture 'A' (4 places).
- Undo and remove screw and nut that clamps plastic light cover at rear of bike (located under seat locking mechanism) and remove plastic light cover.
- Allow original licence plate holder to drop slightly.
- Disconnect indicator and number plate light plug connectors (mark indicator connectors for reassembly).
- Unbolt and remove barometric pressure sensor that is bolted to original licence plate holder (located close to nut and screw just removed) and disconnect wiring plug-socket.
- Remove original licence plate holder.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



PICTURE 'A'

- If not already fitted, fit the new number plate light to new licence plate holder as shown in picture B.
- Feed red and black wires through 8mm central hole in new licence plate bracket, position light so LED's point downwards toward position of licence plate, position threaded spigots through 4mm holes and using nuts and washers tighten new number plate light as shown in picture B.
- **PLEASE NOTE YOU WILL NEED TO GLUE THE LIGHT SHROUD TO THE LED LICENCE PLATE LIGHT BEFORE FITTING USING SUPER GLUE.**
- Feed red and black number plate wires through heat shrink supplied in new kit. Push heat shrink over wires until wires are covered from light unit end and heat gently until it grips wires (**DO NOT OVER-HEAT**).
- If re-using original indicators (these will only fit as shown in picture C) remove from original licence plate holder and reconnect to the new licence plate support bracket (under-tray) place on the same side and use the same fixing method as original.



PICTURE 'B'



PICTURE 'C'



PICTURE 'D'

- If fitting mini's R&G product code RG370 (if using these no resistors are required) you can fit these in either position shown with lens colours as arrowed in picture D.



PICTURE 'E'




PICTURE 'F'

- Secure new licence plate bracket to new licence plate support bracket/under-tray, using the four M5x20mm long button head bolts with washers as shown in picture E (you will have to feed cables through slot in new licence plate support bracket/under-tray).
- On the reverse side fit the M5 nuts and washers over exposed ends of bolts.
- Place the remaining M5 bolt and washer through the barometric sensor, fit the smaller spacer from kit over exposed end of thread and secure to the strengthening plate in licence plate support bracket/under-tray as shown in picture F (the barometric sensor pick up spigot points downwards and must be free from obstruction).
- If fitting a full size licence plate with original or high level exhausts it may be required to space exhaust mounting brackets using larger spacers from kit as shown in picture G.
- Resting new licence plate holder on rear wheel reconnect indicators, rear light and number plate light as original, (**suggest cutting connector/plug from original cable unit approx 75mm from plug end and splicing to R&G unit using connectors supplied**).
- Offer new licence plate holder up into position as original unit.
- It is worth checking operation of all lights and indicators at this stage.
- Using the two M6 bolts, washers and nyloc nuts secure the assembled unit onto rear sub-frame as shown in picture H.
- Ensuring top holes line up with original holes in rear sub-frame, fit rear seat panels and secure using original panel bolts.


R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



PICTURE 'G'



PICTURE 'H'

- Refit number plate (may require drilling).
- Refit seat.
- Depending on local laws, attach enclosed red reflective tape in an appropriate location.
- Test the indicators, licence plate illuminator and all lights before riding.
- **IMPORTANT: IF FITTING A FULL-SIZE LICENCE PLATE AND PLACING IT FAR DOWN ON THE LICENCE PLATE HANGER, THERE IS A SMALL CHANCE OF THE LICENCE PLATE HITTING THE BACK WHEEL UNDER HEAVY LOAD AND OVER LARGE BUMPS IN THE ROAD. IT IS YOUR RESPONSIBILITY TO CHECK FOR THIS POSSIBILITY AND TAKE AVOIDING ACTION. FAILURE TO CHECK THIS COULD RESULT IN SERIOUS INJURY.**

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com